




Flameshield™ FireDuct Access Doors



Technical Data Sheets



Product Code Product Dimensions

FP2020	200mm x 200mm
FP3015	300mm x 150mm
FP3030	300mm x 300mm
FP4020	400mm x 200mm
FP4040	400mm x 400mm
FP4530	450mm x 300mm
FP4545	450mm x 450mm
FP6060	600mm x 600mm

Standards

Fire Resistant BS EN 1366-1:1999
Test
BS 476 Part 24 2 hours
Test Report No 274223

Description

Kent Ductwork's range of Flameshield™ FireDuct's Access Doors are designed to be installed into Fire Rated Ductwork systems, both insulated and non insulated for the purpose of internal inspection and access for cleaning purposes without compromising the integrity of the Fire rating. They can be installed into all Fire Rated systems. Each fire rated access door is supplied with an installation frame and removable panel, the panel is secured in place using cam locks. The installation frame is mechanically fixed to the duct by 3.97mm (5/32") diameter steel rivets at 70 mm pre drilled centers. A 20mm x 5mm thick ceramic felt strip provides an airtight, fire resistant seal between the panel and the installation frame, the installation frames incorporates an 8mm internal grease trap. Each Door is stamped with the Flameshield™ Logo. Door can be supplied with a supporting plastic coated (red) wire that can be attached to the ductwork away from the working area.

Materials

Internal panel	Mineral Fibre
insulation	25mm - 100kg m2
Gasket	Ceramic Paper, adhesive one side 20 mm x 5 mm
Cam Lock	Bright Zinc Plate
Panel	Galvanised Steel BS EN 10142
Keeper	Galvanised Steel
Fixings	4.65/4.77 x 4.75/5.00 Mild Steel oval head semi tubular rivet



Certified to BS 476
Part 24 Cert. No. 785a



Cert. No. 785

Kent Ductwork Ltd.
Units 7-9 Swaislands Drive
Crayford Ind Est
Crayford T: +44(0)1322 558887
Kent E: info@kentductwork.co.uk
United Kingdom www.kentductwork.co.uk
DA1 4HS

Page 1 of 1

Drawing No | Various

Date | 20. 03.2012

Document | QA: FS AD TDS

Rev | Rev 0