

CFI IN-LINE 

CFI IN-LINE

In addition to our “standard range” filters. CF-Industrial created In-Line filters with an addition housing around the carbon filter.

care for air!

FILTER	MATERIAL	CARBON	LENGTH	WEIGHT CARBON	WEIGHT TOTAL	DIAMETER	CARBON BED	CAPACITY PRACTICAL	POS. FLANGES
CFI in-Line 3000	Galva	Lite	110cm	14,3 kg	40,5 kg	45 cm	5 cm	3000 m ³	315
CFI in-Line 2500	Galva	Lite	110 cm	12,2 kg	34,5 kg	40 cm	5 cm	2500 m ³	250/315
CFI in-Line 1500	Galva	Lite	87 cm	7,6 kg	24 kg	35 cm	5 cm	1500 m ³	250/200
CFI in-Line 1000	Galva	Lite	62 cm	5,1 kg	17 kg	35 cm	5 cm	1000 m ³	250/200
CFI in-Line 600	Galva	Lite	60 cm	2,2 kg	10 kg	30 cm	3,5 cm	600 m ³	125/150/160
CFI in-Line 425	Galva	Lite	72,5 cm	1,9 kg	12 kg	30 cm	2,5 cm	425 m ³	100/125
CFI in-Line 300	Galva	Lite	56,5 cm	1,8 kg	10 kg	30 cm	2,5 cm	300 m ³	100/125
CFI in-Line 150	Galva	Lite	37 cm	1,2 kg	8 kg	30 cm	2,5 cm	150 m ³	100/125



This In-Line model offers added product value for the following reasons:

1. Easy to maintain in between ducting material, due to his double flange connection and addition housing
2. Directly connectable to heat recovery systems. For capturing gasses directly from the semi-closed airstream.
3. Available in various sizes, for all kind of airflows
4. Available also with various types of carbon. In case specific gases occurs.
5. In case harmful gasses occur. The carbon filters will not be exposed during replacement. Due to the fact, you are only in contact with the external housing.