

## Represented by:

### ELTA FANS LTD (BUILDING SERVICES)

Tel: +44 (0)1384 275800 Fax: +44 (0)1384 275810 email: sales@eltafans.co.uk 46 Third Avenue, Pensnett Trading Estate, Kingswinford, West Midlands DY6 7US, UK

Version 5.21.12 Copyright © 2010-19 Elta Group

## Technical Data - Fan Model SMT125 (High speed)

Location: Designation:

Verify stock availability for life of quotation.

#### 

Air Flow: 0.00 m³/s Air Flow: 0.00 m³/s Static Pressure: 0 Pa Static Pressure: 0 Pa Total Pressure: 0 Pa

Installation Type: n/a

Air Density: 1.204 kg/m³
- Atmos. Temp: 20 °C
- Altitude: 0 m
- Humidity: 0.0 %

#### **Fan Data**

Catalogue Code: SMT125 (High speed)
Description: Inline Mixed-Flow

Diameter: 125 mm Impeller Type: Mixed Flow

Blade Material:

Speed: 2330 r/min @50 Hz

Power, Abs: - Peak:

Input Power: 0.02 kW

Efficiency Total: - Static: -

SFP: -


Fan Weight: 3.0 kg
Motor Data (at STP)


Motor Type:

Electrical Supply: 230V 1ph 50Hz

Motor Frame:

Motor Power: 0.03kW FLC/Start: 0.18A / - Motor Speed: 2 pole Motor Efficiency: -





#### **Sound Data**

Spectrum (Hz):	63	125	250	500	1K	2K	4K	8K	dBW	dB(A) @ 3m
Inlet (dB):	57	59	70	69	65	63	57	52	74	50

Sound levels are quoted as in-duct values. dB(A) values are average spherical free-field for comparative use only.



# Represented by: ELTA FANS LTD (BUILDING SERVICES)

Tel: +44 (0)1384 275800 Fax: +44 (0)1384 275810 email: sales@eltafans.co.uk 46 Third Avenue, Pensnett Trading Estate, Kingswinford, West Midlands DY6 7US, UK

Version 5.21.12 Copyright © 2010-19 Elta Group


## Technical Data - Fan Model SMT125 (High speed)


Location: Designation:

**Energy Related Product Data** 

At Maximum Efficiency Point
Overall Efficiency: 15.8% Input Power: 0.02 kW
Measurement Category: C Air Flow: 0.04 m³/s
Efficiency Category: Static Pressure: 102 Pa
FMEG: 0 Speed: 2330 r/min
Specific Ratio: 1

## **Drawing for Fan Model SMT125**





PRODUCT DUCT	А	В	С	D	E	F	G	WEIGHT KG.
SMT100	315	235	115	98	180	232	130	3
SMT125	280	235	115	122	180	232	130	3
SMT150	294	270	115	147	192	240	130	3
SMT200	354	265	140	197	230	280	142	4