



A Skellerup Industries Company

It's so easy with a Dektite® EZi-Seal™

Dektite® EZi-Seal™ Hang-sell

Dektite® EZi-Seal™ products are now available in individual hang-sell packs with printed instructions and fasteners included.



Forget silicone – just screw it down

Dektite® EZi-Seal™ features a revolutionary closed-cell foam gasket which is non-absorbant and non-porous. It hugs the roof line to provide a watertight seal without the need for silicone.

CHECK THE BENEFITS!

- Meets the toughest conditions
The foam base will not react with polycarbonate roofing
- No worries on polycarbonate
No silicone means no slippery surface or mess
- Safer on the roof
No need to clean or prepare the surface
- Seals on wet or oily surfaces
Seals completely waterproof at only 40% compression
- 100% waterproof
No silicone to apply - just screw it down in minutes
- Installs faster! Up to 30%
UV, ozone and temperature resistant foam



FS 52067
QUALITY ISO9001
AS/NZS 4347

www.deks.com.au

Installation Instructions



1

Trim the cone to suit pipe size using sharp tin snips.




2

Slide down pipe using water as lubricant.




3

Press base to the roof profile by hand.



4

Fasten using self-sealing fasteners or pop (sealed) rivets.



*

Use Dektite® EZi-Seal™ on the 'diamond' or bias for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations.

EASY SELECTION GUIDE

Features a revolutionary non-absorbent and non porous sponge gasket that seals by compression, even in wet conditions, it hugs the roof line to provide a watertight seal without the need for silicone adhesive.

Code No	Pipe External	Base mm	Pitch	
DFE 0-35EZ	0-35MM	0-3/8"	99 X 99	0-60° OR 1 1/2
DFE 5-55EZ	5-55MM	1/4 - 2 1/8"	137 X 137	0-45° OR 1 1/2
DFE 50-70EZ	50-70MM	2 - 2 3/4"	178 X 178	0-45° OR 1 1/2
DFE 5-120EZ	5-120MM	1/4 - 4 3/4"	218 X 218	0-45° OR 1 1/2
DFE 160-220EZ	160-220MM	6 1/4 - 8 3/4"	365 X 365	0-45° OR 1 1/2
DFE 160-300EZ	160-300MM	6 1/4 - 11 3/4"	453 X 453	0-45° OR 1 1/2
DFE 290-440EZ	290-440MM	11 1/2 - 17 3/8"	581 X 581	0-45° OR 1 1/2

Black (EPDM)*

Available in Black EPDM

E.P.D.M. Withstands temperatures from -50° C to 115° C & up to 150° C intermittently.

E.P.D.M. Withstands temperatures from -58° F to 239° F, & up to 302° F intermittently.

EPDM - Perfect for approved flues!

Dektite® EPDM polymer flashings have been officially tested by the Coal Corporation of Victoria, Australia and conform to all Australian and UK Standards on approved flue systems. Under no circumstances should any polymer flashing be installed on a non approved flue or an 'active' combustion heater flue.


FASTENING METHODS



Corrugated Roof



Tray Roof with Standard Rib




Tray Roof with High Rib

Dektite® EZi-Seal™ seals by compression, so ensure fasteners are evenly distributed (approx. every 40mm) around base. It is also essential that fasteners are placed in any valleys created when product forms around a roof ridge.



Fix Fasteners at points where base has creased to confirm to roof profile.

On some roof profiles, such as Kliplok, an extra fastener is needed where it indents at the top of the ridge (see right).



- Use 10x16 Hex head self-drilling fasteners.
- After screw-fixing the base, flatten the aluminium between the fixings to compress the foam.
- Always install a fixing into the corners of the profile to fully seal against the sheet.
- Make sure the foam is compressed by at least 40% all the way round to ensure an effective seal.

IMPORTANT

Silicone does not affect the foam gasket